



### SureBond Joint and Crack Filler Mortar



#### Applications:

- For filling cracked masonry and mortar.

#### Benefits:

- Fills cracks between 0.5mm and 25mm.
- For interior and exterior use.
- Absorbs natural building movement.
- Flexible and cement free.
- Clean to use.
- Easy flowing.
- Suitable for masonry, concrete, masonry, plaster and stone.
- Seals cracks to prevent water penetration.
- Water-proof.
- Can be covered with render or paint after fully hardening
- Used with a standard mastic gun



#### Instructions

Prior to injecting SureFill, the edges of the joints and cracks must be thoroughly cleaned and moistened. Inject the SureFill as deep as possible into the joint or crack and fill to the surface. Each tube will fill approx. 350 cm<sup>3</sup>.

The curing time of the SureFill takes proportionally longer as wider and deeper a crack is. The high value of dispersion avoids shrinkage and enhances flexibility, but this means also, that it takes longer for the curing.

With a crack width of 2cm and a depth of 3 cm and a temperature of approx. 10°, it can take up to 1 – 2 weeks to fully cure. For small cracks (5mm or less) and a temperature of approx. 20°, it cures in 1 – 2 days.

Clean your working equipment immediately after use with water.

Colour – Beige  
Working temperature +5°C and above.  
Fills cracks between .5mm and 25mm  
For interior and exterior use.  
Store in a cool, frost-free environment.  
Tube Contents 310ml

**SUREFILL HAS A NON HAZARD CLASSIFICATION**

**CONSTRUCTION PRODUCTS SOLUTIONS INTERNATIONAL LTD.**

Unit 3, Haslemere Industrial Estate, Pig Lane, Bishop's Stortford, Hertfordshire. CM23 3HG. United Kingdom.  
Tel: +44(0)1279 505 514 - Fax: +44(0)1279 755190 - e mail: [info@surecps-group.com](mailto:info@surecps-group.com) - [www.surecps-group.com](http://www.surecps-group.com)  
Company Reg. 6969591 VAT Reg. GB 824 4246 40

