

CPSI Anchor Grout S / Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 1/9

CPSI anchor grout S/ anchor grout R / anchor grout F

1. Identification of Substance/Preparation and Company

- 1.1. Information on the product Trade Name: CPSI anchor grout S/ anchor grout R / anchor grout F
- 1.2. Use of the substance /preparation Factory prepared dry mortar
- 1.3. Identification of the manufacturer/supplier Supplier:

CPSI Limited Unit 3, Haslemere Industrial Estate Pig Lane Bishop's Stortford Hertfordshire CM23 3HG United Kingdom. Telephone No +44(0)1279 505514 Telefax +44(0)1279 755190 E-mail: info@surecps-group.com www.surecps-group.com Company Reg. 6969591 VAT Reg. GB 824 4246 40 +44(0)1279 505514 (Office hours 0800 - 1700 Mon - Fri then diverts to an appropriate call centre)

Emergency information:

2. Hazards Identification

2.1 Classification

Classification (according to GHS):

Class	Hazard class
Skin irritant (Skin Irrit.)	2
Eye damage (Eye Dam.)	1
Specific target organ toxicity – single exposure (STOT SE)	3

Classification (according to 1999/45/EC):

R-phrase	Name
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes

2.2 Labelling Labelling (GHS): Symbol(s):



CONSTRUCTION PRODUCTS SOLUTIONS INTERNATIONAL LTD.

Unit 3, Haslemere Industrial Estate, Pig Lane, Bishop's Stortford, Hertfordshire. CM23 3HG. United Kingdom. Tel: +44(0)1279 505 514 - Fax: +44(0)1279 755190 - e mail: info@surecps-group.com - www.surecps-group.com Company Reg. 6969591 VAT Reg. GB 824 4246 40





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 2/9

P code	Precautionary statements
P102	P102 Keep out of reach of children. ¹⁾
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P305+P351+P338+P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P302+P352+P333+P313	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
P261+P304+P340+P312	Avoid breathing dust. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P501	Dispose of contents/containers at hazardous or special waste collection point. ¹⁾
¹⁾ Only when sold to private	consumers
Hazardous components (la	abelling)
Contains Portland cement	

EC No.: 266-043-4

Labelling (according to 67/548/EEC):

R-phrase	ase Name	
R37/38	Irritating to respiratory system and skin.	
R41	Causes serious eye damage	
¹⁾ Only when sold to private consumers		
Hazardous components (labelling)		
Contains Portland cement		
S-phrase	Name	
S 24/25	Avoid eye and skin contact	
S 22	Do not inhale dust	
S 26 In case of contact with skin or eyes, rinse immediately with water and seek medical advice		
S 36/37/39	Wear suitable protective clothing, gloves and eye/face protection	
S 46	If swallowed, seek medical advice immediately and show this container or label	

EC No.: 266-043-4





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 3/9

2.3 Other hazards

Gives an alkaline reaction with moisture. Once mixed with water, the product can cause serious skin damage on prolonged contact (e. g. when kneeling in moist mortar) due to its alkalinity. Store in a cool, dry place. Inappropriate storage (contact with humidity) or storage past the expiration date may reduce the effectiveness of the contained chromate reducer. In this case, a sensitization due to skin contact cannot be excluded.

3. Composition / Specification of Components

3.1. Chemical characterization (preparation) Description: Cement, quartz sand, additives

3.2 Hazardous components

EC No. REACH No.	CAS No.	Substance	Content (%)	Classification*	Remark
<u>266-043-4 Xi</u>	65997-15-1	Portland cement	15-25%	Xi <u>R 37/38-41</u> 3.2./2/H315 3.3/1/H318 3.8/3/H335	(1)

(1) = Substance hazardous to health or environment

- (2) = Substance with a Community workplace exposure limit
- (3) = PBT substance
- (4) = vPvB substance
- (5) = SVHC candidate (substance of very high concern)

* For information on classification refer to section 16

3.3 Additional information

The preparation is low in chromate, since the content of sensitising chromium (VI) is reduced to less than 2 ppm by additives to the cement parts of the ready-to-use mortar. The prerequisite for the effectiveness of the chromium reduction is appropriate storage and observance of the shelf-life (see section 7.2).

4. First Aid Measures

4.1. General information

Remove persons to safe areas. Respect self-protection of the first aider.





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 5 Page: 4/9

4.2. After inhalation

Supply fresh air. In case of complaints, seek immediate medical advice.

4.3. After skin contact

Rinse with plenty of water, change contaminated clothing immediately.

4.4. After eye contact

Do not rub the eyes dry. If necessary, remove contact lenses and rinse eyes immediately with running water keeping the eyelids open (for about 20 minutes). Always consult an ophthalmologist.

4.5. After ingestion

Drink plenty of water in small portions drink (only if person is conscious). Do not induce vomiting. Seek medical advice and clearly identify substance.

4.6. Advice to doctor

Product reacts alkaline when in contact with moisture. May cause skin irritation or chemical burns to mucous membranes.

5. Fire-Fighting Measures

- **5.1** Suitable extinguishing media The product is not flammable. Adapt extinguishing measures to surrounding fire.
- 5.2 Extinguishing media which must not be used for safety reason. none
- 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: none.
- 5.4 **Protective equipment** Use self-contained respirator.

6. Accidental Release Measures

- 6.1 Personal precaution measures Wear personal protective equipment (refer to section 8). Keep unprotected persons away. Avoid eye and skin contact. Avoid inhalation of dust.
- 6.2 Environmental precautions Do not allow to enter sewers, surface or ground water.





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 5/9

- 6.3 Methods for cleanup and containment Clean up dry powder and mixed product mechanically and dispose of it properly.
- 6.4 Additional information
- 7. Handling and Storage
- 7.1 Handling

Information on safe handling Avoid dust formation. In case of dust formation, take appropriate protective measures (exhaust/ ventilation, respiratory protection). Provide adequate ventilation at the workplace. Information on fire and explosion protection none

- 7.2 Storage Requirements for storage rooms and containers: none known.
- 7.2.2 Information on storage with other products Store away from acids.
- 7.2.3 Further information on storage conditions:

Store in a cool, dry place. Inappropriate storage (contact with humidity) or storage past the expiration may reduce the effectiveness of the contained chromate reducer. In this case, a sensitization due to skin contact cannot be excluded.

7.2.4 Storage category

VCI storage category 13; non-flammable solid material

8. Explosion Limits and Personal Protective Equipment

8.1 Exposure limits values

CAS No.	Substance	Туре	mg/m ³	ppm
65 997-15-1	Portland cement	MAK value	5	
14808-60-7	Quartz		0.15 (A)	

The MAK value (German maximum workplace concentration) for respirable quartz-containing dusts which may result from the processing of powdered quartz-containing preparations in general, is generally 0.15 mg/m³. A particulate matter concentration of 6 mg/m³ is set as a general dust limit value.





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 6/9

8.2 Occupational exposure control General protective and hygienic procedures: Avoid eye and skin contact. Do not eat, drink or smoke at work. Do not inhale dust. Wash exposed body parts after handling and apply moisturizing cream to prevent dermatitis. **Respiratory protection:** If the exposure threshold values are exceeded, wear particle-filtering half mask FFP1 (white). (see code of practice leaflet BGR 190 2) Hand protection: Wear suitable gloves, e. g., nitrile impregnated cotton gloves. Eye protection: Wear tightly sealed goggles **Body protection:** Wear suitable protective clothing. **Skin Protection:** Skin protection plan in accordance with code of practice leaflet BGR 197 2.

8.2.2 Limitation and monitoring of exposure to the environment Prevent material from entering surface waters, drains, sewers or soils.

8.3 Additional information on design of technical facilities Observe information in section 7.

9. Physical and Chemical Properties

9.1	General information.			
	Physical state / shape	Powder		
	Colour	Grey		
	Odour	Odourless		

9.2 Safety-relevant data

Melting point Boiling Point Flash point: Ignition temperature: Explosion group Explosion limits Vapour pressure Density Bulk density Solubility in water pH value Partition coefficient octanol / water Dynamic viscosity not determined not determined product is not flammable product is not flammable product is not explosible not available not determined not determined not determined < 2g/l Approx. 12 at 25°C (500 g/l H20) not determined not determined





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 7/9

- 9.3 Further information
- 10. Stability and Reactivity
- **10.1 Conditions to avoid** Contact with moisture
- 10.2 Materials to avoid Acid wastes
- **10.3 Hazardous decomposition** If stored and handled properly: none known.
- 10.4 Hazard reactions Risk of dust explosion, explosion class St1
- 11. Toxicology Data
- 11.1 General

Virtually all studies based on experiments with animals, as well as practical experience (epidemiological studies), describe irritant and inflammatory reactions, especially in the upper respiratory tract, after exposure to cement dust. The frequently observed obstructive changes to the airways are associated with the chemical irritant effect (the high alkalinity) of cement dust.

11.2 Toxicological tests

No toxicological tests have been made on animals for this preparation.

11.3 Additional toxicological information

Once mixed with water, the product can cause serious skin lesions and damage to the eyes on prolonged contact due to its alkalinity. At the same time mechanical wear to the skin can exacerbate such effects. As long as the expiration date of the grey Portland cement is not exceeded, no sensitizing effect is to be expected.

- 12. Ecological information
- 12.1 Environmental toxicity
- **12.2** Information on elimination (persistence and degradability) Not biodegradable, since preparation consists of mineral substances

12.3 Additional ecological information

Prevent material from entering surface waters, drains, sewers or soils. May increase the pH value.





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 8/9

13. Information on disposal

13.1 Product

Waste code number: 010410 (dusty and powdery wastes other than those mentioned in 01 04 07.) or Mix with water, allow to harden, then dispose of as construction waste. Waste code number: 17 01 07 (pure construction waste) or 170904 (mixed construction waste, without hazardous substances)

13.2 Uncleaned packaging

Recommendation: Empty packaging completely. Reuse or recycle containers preferably, in compliance with the applicable local regulations.

14. Transport Regulations

 14.1
 Land transport GGVSE / ADR and RID

 ADR
 Assessment

 Non-hazardous good according to transport regulations

Assessment	Non-nazardous good according to transport regulations
Assessment	Non-hazardous good according to transport regulations

- 14.2 Air transport ICAO-TI and IATA-DGR

 Assessment
 Non-hazardous good according to transport regulations
- 14.3 Marine transport IMDG/GGVSea

 Assessment
 Non-hazardous good according to transport regulations

14.4 Transport/further information

15. Regulatory Information

15.1 National regulations

Information on employment limitations

TA-Luft (German technical instructions on air quality control): Clause 3.1.5 German water hazard classification (WGK) WGK 1 – slightly hazardous to water (self-classification) Further regulations Chemical safety assessment For this product is no chemical safety assessment available.

15.2 Further international regulations

- Information on the international registration status





CPSI Anchor Grout S/ Anchor Grout R / Anchor Grout F Version 1.13 Printing date: 16.04.2015 12:19, revised on 16.04.2015 07:45 Page: 9/9

16. Further Information

16.1 Product

All details given are based at our present knowledge and are designed to describe our product with regard to health & safety requirement. However, they are not intended to guarantee any characteristics of the product described in terms of statutory warranty regulations. It is the responsibility of the user of our product to comply with existing laws, regulations and standards.

16.2 Additional information

